

Этикетки для принтера BMR41

Технические характеристики

По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +(727)345-47-04

Беларусь +(375)257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: byb@nt-rt.ru || сайт: <https://brady.nt-rt.ru/>

Save with Printer Starter Kits



Catalog #	Kit Contents
BMP41 DataComm Starter Kit (BMP41-KIT-VD)	1 - BMP41 Label Printer Standard Package (BMP41-KIT) 1 - BMP41 Hard Case (BMP41-HC) 1 - 1.0 in. black on white B-427 cartridge (M-51-427) 1 - 0.475 in. black on white B-412 cartridge (MC-475-412) 1 - 1.0 in. black on yellow B-595 cartridge (MC1-1000-595-YL-BK) 1 - 1.0 in. black on white B-595 cartridge (MC1-1000-595-WT-BK)
BMP41 Electrical Starter Kit (BMP41-KIT-EL)	1 - BMP41 Label Printer Standard Package (BMP41-KIT) 1 - BMP41 Hard Case (BMP41-HC) 1 - 1.0 in. black on white B-427 cartridge (M-143-427) 1 - 1.0 in. black on white B-498 cartridge (M-48-498) 1 - 0.75 in. black on white B-342 cartridge (M-187-075-342) 1 - 1.0 in. black on orange B-595 cartridge (MC1-1000-595-OR-BK) 1 - 1.0 in. black on white B-595 cartridge (MC1-1000-595-WT-BK)
BMP41 Facility ID Starter Kit (BMP41-KIT-GI)	1 - BMP41 Label Printer Standard Package (BMP41-KIT) 1 - 1.0 in. black on yellow B-595 cartridge (MC1-1000-595-YL-BK) 1 - 1.0 in. red on white B-595 cartridge (MC1-1000-595-WT-RD) 1 - 1.0 in. white on green B-595 cartridge (MC1-1000-595-GN-WT) 1 - 1.0 in. black on white B-595 cartridge (MC1-1000-595-WT-BK) 1 - 1.0 in. black on white B-483 cartridge (M-60-483)

*Printer ships with BMP41 rechargeable battery pack, MC1-1000-595-WT-BK cartridge, USB cable, AC adapter, product CD, printer drivers CD, quick start guide and 2-year warranty.

Indoor and Outdoor Vinyl for Safety, Facility and Lean 5S (B-595)

Continuous vinyl material is ideal for lean 5S labels, pipe markers, equipment and production area identification. These labels offer excellent resistance to oils, detergents, dirt, grime and many solvents. Permanent adhesive, very pliable, good for rough surfaces and outdoor use. 8-10 years average outdoor durability.* Temp. range: -40° F to 180° F (-40° C to 82° C). UL recognized.



Figure 33



Fits Printers	Figure	Catalog #	B#	Material	Color	Label Width A Inch (mm)	Roll Length B Feet (m)	Labels Per Roll	Ribbon in Cartridge
BMP41, 51, 53	Fig. 33	MC-375-595-WT-BK	B-595	Vinyl	BK on WT	0.375 (9.5)	25 (7.6)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC-500-595-WT-BK	B-595	Vinyl	BK on WT	0.500 (12.7)	25 (7.6)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC-750-595-WT-BK	B-595	Vinyl	BK on WT	0.750 (19.1)	25 (7.6)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC1-1000-595-WT-BK	B-595	Vinyl	BK on WT	1.000 (25.4)	25 (7.6)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC-375-595-YL-BK	B-595	Vinyl	BK on YL	0.375 (9.5)	25 (7.6)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC-500-595-YL-BK	B-595	Vinyl	BK on YL	0.500 (12.7)	25 (7.6)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC-750-595-YL-BK	B-595	Vinyl	BK on YL	0.750 (19.1)	25 (7.6)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC1-1000-595-YL-BK	B-595	Vinyl	BK on YL	1.000 (25.4)	25 (7.6)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC-500-595-OR-BK	B-595	Vinyl	BK on OR	0.500 (12.7)	25 (7.6)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC-750-595-OR-BK	B-595	Vinyl	BK on OR	0.750 (19.1)	25 (7.6)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC1-1000-595-OR-BK	B-595	Vinyl	BK on OR	1.000 (25.4)	25 (7.6)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC-500-595-BL-WT	B-595	Vinyl	WT on BL	0.500 (12.7)	25 (7.6)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC-750-595-BL-WT	B-595	Vinyl	WT on BL	0.750 (19.1)	25 (7.6)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC1-1000-595-BL-WT	B-595	Vinyl	WT on BL	1.000 (25.4)	25 (7.6)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC-375-595-RD-WT	B-595	Vinyl	WT on RD	0.375 (9.5)	25 (7.6)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC-500-595-RD-WT	B-595	Vinyl	WT on RD	0.500 (12.7)	25 (7.6)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC-750-595-RD-WT	B-595	Vinyl	WT on RD	0.750 (19.1)	25 (7.6)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC1-1000-595-RD-WT	B-595	Vinyl	WT on RD	1.000 (25.4)	25 (7.6)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC-500-595-GN-WT	B-595	Vinyl	WT on GN	0.500 (12.7)	25 (7.6)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC-750-595-GN-WT	B-595	Vinyl	WT on GN	0.750 (19.1)	25 (7.6)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC1-1000-595-GN-WT	B-595	Vinyl	WT on GN	1.000 (25.4)	25 (7.6)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC-500-595-WT-RD	B-595	Vinyl	RD on WT	0.500 (12.7)	25 (7.6)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC-750-595-WT-RD	B-595	Vinyl	RD on WT	0.750 (19.1)	25 (7.6)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC1-1000-595-WT-RD	B-595	Vinyl	RD on WT	1.000 (25.4)	25 (7.6)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC-500-595-BK-WT	B-595	Vinyl	WT on BK	0.500 (12.7)	25 (7.6)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC-750-595-BK-WT	B-595	Vinyl	WT on BK	0.750 (19.1)	25 (7.6)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC1-1000-595-BK-WT	B-595	Vinyl	WT on BK	1.000 (25.4)	25 (7.6)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC-500-595-CL-BK	B-595	Vinyl	BK on CL	0.500 (12.7)	20 (6.09)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC-750-595-CL-BK	B-595	Vinyl	BK on CL	0.750 (19.1)	20 (6.09)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC1-1000-595-CL-BK	B-595	Vinyl	BK on CL	1.000 (25.4)	20 (6.09)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC-500-595-CL-WT	B-595	Vinyl	WT on CL	0.500 (12.7)	20 (6.09)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC-750-595-CL-WT	B-595	Vinyl	WT on CL	0.750 (19.1)	20 (6.09)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC1-1000-595-CL-WT	B-595	Vinyl	WT on CL	1.000 (25.4)	20 (6.09)	1 roll (cont.)	R4400

* Average expected outdoor life of product will depend on user definition of failure, climatic conditions, mounting techniques and material color. The 8 to 10 year outdoor durability applies to the vinyl label stock only; ribbon durability will vary.

Bin, Storage, Reflective and General Industrial Labels (B-422, B-483, B-499, B-584 and B-595)

Several materials with an aggressive adhesive for use in commercial and industrial applications. Reflective materials can be used for low light or inclement weather conditions on outdoor utility poles and pedestals, jobsite equipment and rooftop equipment.

- **B-422 Polyester Material:** Permanent adhesive, good for powder-coated. Best on flat surfaces. Temp. range: -40° F to 212° F (-40° C to 100° C). UL recognized.
- **B-483 Polyester Material:** Permanent adhesive, good for powder-coated. Best on flat surfaces. Temp. range: -40° F to 248° F (-40° C to 120° C). UL recognized.
- **B-499 Nylon Cloth Material:** Permanent adhesive. Pliable for rough or smooth surfaces. Temp. range: -94° F to 194° F (-70° C to 90° C). UL recognized.
- **B-584 Reflective Tape:** Reflective material shines back brightly when struck by light. Meets Federal Spec L-S-300 for reflectivity. Average outdoor durability is 4-6 years. Temp. range: -40° F to 158° F (-40° C to 70° C).
- **B-595 Indoor and Outdoor Vinyl Material:** Permanent adhesive, very pliable, good for rough surfaces and outdoor use, wide range of colors. Temp. range: -40° F to 180° F (-40° C to 82° C). UL recognized.



Figure 2




Figure 33

Fits Printers	Figure	Catalog #	B#	Material	Color	Label Width A Inch (mm)	Label Height B Inch (mm)	Labels Per Roll	Ribbon in Cartridge
B-422 Polyester Material									
BMP41, 51, 53	Fig. 33	MC-375-422	B-422	Polyester	BK on WT	0.375 (9.5)	25 ft. (7.6 m)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC-475-422	B-422	Polyester	BK on WT	0.475 (12.1)	25 ft. (7.6 m)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 2	M-7-422	B-422	Polyester	BK on WT	0.500 (12.7)	0.500 (12.7)	280	R6000
BMP41, 51, 53	Fig. 33	MC-500-422	B-422	Polyester	BK on WT	0.500 (12.7)	25 ft. (7.6 m)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC-625-422	B-422	Polyester	BK on WT	0.625 (15.9)	25 ft. (7.6 m)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 2	M-47-422	B-422	Polyester	BK on WT	1.000 (25.4)	0.500 (12.7)	480	R6000
BMP41, 51, 53	Fig. 2	M-49-422	B-422	Polyester	BK on WT	1.000 (25.4)	1.000 (25.4)	260	R6000
BMP41, 51, 53	Fig. 33	MC1-1000-422	B-422	Polyester	BK on WT	1.000 (25.4)	25 ft. (7.6 m)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 2	M-89-422	B-422	Polyester	BK on WT	1.500 (38.1)	0.500 (12.7)	180	R6000
BMP41, 51, 53	Fig. 2	M-90-422	B-422	Polyester	BK on WT	1.500 (38.1)	0.750 (19.1)	180	R6000
B-483 Ultra-Aggressive Polyester									
BMP41, 51, 53	Fig. 2	M-47-483	B-483	Polyester	BK on WT	1.000 (25.4)	0.500 (12.7)	480	R6000
BMP41, 51, 53	Fig. 2	M-60-483	B-483	Polyester	BK on WT	2.000 (50.8)	1.000 (25.4)	140	R6000
B-499 Nylon Cloth Labels									
BMP41, 51, 53	Fig. 33	MC-375-499	B-499	Nylon Cloth	BK on WT	0.375 (9.5)	16 ft. (4.9 m)	1 roll (cont.)	R4300
BMP41, 51, 53	Fig. 33	MC-500-499	B-499	Nylon Cloth	BK on WT	0.500 (12.7)	16 ft. (4.9 m)	1 roll (cont.)	R4300
BMP41, 51, 53	Fig. 2	M-11-499	B-499	Nylon Cloth	BK on WT	0.750 (19.1)	0.500 (12.7)	220	R4300
BMP41, 51, 53	Fig. 33	MC-750-499	B-499	Nylon Cloth	BK on WT	0.750 (19.1)	16 ft. (4.9 m)	1 roll (cont.)	R4300
BMP41, 51, 53	Fig. 2	M-130-499	B-499	Nylon Cloth	BK on WT	0.825 (20.9)	0.375 (9.5)	220	R4300
BMP41, 51, 53	Fig. 2	M-84-499	B-499	Nylon Cloth	BK on WT	0.900 (22.8)	0.500 (12.7)	200	R4300
BMP41, 51, 53	Fig. 2	M-131-499	B-499	Nylon Cloth	BK on WT	1.000 (25.4)	0.500 (12.7)	180	R4300
BMP41, 51, 53	Fig. 2	M-128-499	B-499	Nylon Cloth	BK on WT	1.000 (25.4)	1.900 (48.3)	100	R4300
B-584 Reflective Tape									
BMP41, 51, 53	Fig. 33	MC-500-584	B-584	Reflective	BK on WT	0.500 (12.7)	20 ft. (6.1 m)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC-750-584	B-584	Reflective	BK on WT	0.750 (19.1)	20 ft. (6.1 m)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC-500-584-YL	B-584	Reflective	BK on YL	0.500 (12.7)	20 ft. (6.1 m)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC-750-584-YL	B-584	Reflective	BK on YL	0.750 (19.1)	20 ft. (6.1 m)	1 roll (cont.)	R6000
B-595 Indoor and Outdoor Vinyl Tape									
BMP41, 51, 53	Fig. 33	MC-500-595-RD-WT	B-595	Vinyl	WT on RD*	0.500 (12.7)	25 ft. (7.6 m)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC-750-595-RD-WT	B-595	Vinyl	WT on RD*	0.750 (19.1)	25 ft. (7.6 m)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC1-1000-595-RD-WT	B-595	Vinyl	WT on RD*	1.000 (25.4)	25 ft. (7.6 m)	1 roll (cont.)	R4400

* For additional general purpose tapes in other colors, refer to the indoor and outdoor grade facility and safety labels on page 109.

BMP41 cartridges

The necessary print ribbons for the BMP41 Label Printer are self-contained within the label roll cartridge.

No need to order or load separate print ribbons.



Inside-Panel Component Labels for Electrical and Automation Applications (B-422, B-428, B-483, B-499 and B-595)

Variety of durable materials ideal for marking backer boards, DIN rail, relays, PLCs, switches and solenoids. Create serial or rating plates with barcodes, graphics and more with a flexible high-tack adhesive for easy and long-lasting adhesion.

- **B-422 Polyester Material:** Permanent adhesive, good for powder-coated / textured surfaces. Best on flat surfaces. Temp. range: -40° F to 212° F (-40° C to 100° C). UL recognized.
- **B-428 Metallized Polyester Material:** Permanent adhesive, silver finish. Temp. range: -40° F to 176° F (-40° C to 80° C). UL recognized.
- **B-483 Polyester Material:** Permanent adhesive, good for powder-coated / textured surfaces. Best on flat surfaces Temp. range: -40° F to 248° F (-40° C to 120° C). UL recognized.
- **B-499 Nylon Cloth Material:** Permanent adhesive. Pliable for rough or smooth surfaces. Temp. range: -94° F to 194° F (-70° C to 90° C). UL recognized.
- **B-595 Indoor and Outdoor Vinyl Material:** Permanent adhesive, very pliable, good for rough surfaces and outdoor use, wide range of colors. Temp. range: -40° F to 180° F (-40° C to 82° C). UL recognized.




Figure 2

Figure 3

Fits Printers	Figure	Catalog #	B#	Material	Color	Label Width A Inch (mm)	Label Height B Inch (mm)	Labels Per Roll	Ribbon in Cartridge
B-422 Polyester Material									
BMP41, 51, 53	Fig. 33	MC-375-422	B-422	Polyester	BK on WT	0.375 (9.5)	25 ft. (7.6 m)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC-475-422	B-422	Polyester	BK on WT	0.475 (12.1)	25 ft. (7.6 m)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 2	M-7-422	B-422	Polyester	BK on WT	0.500 (12.7)	0.500 (12.7)	280	R6000
BMP41, 51, 53	Fig. 33	MC-500-422	B-422	Polyester	BK on WT	0.500 (12.7)	25 ft. (7.6 m)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC-625-422	B-422	Polyester	BK on WT	0.625 (15.8)	25 ft. (7.6 m)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 2	M-47-422	B-422	Polyester	BK on WT	1.000 (25.4)	0.500 (12.7)	480	R6000
BMP41, 51, 53	Fig. 2	M-49-422	B-422	Polyester	BK on WT	1.000 (25.4)	1.000 (25.4)	260	R6000
BMP41, 51, 53	Fig. 33	MC1-1000-422	B-422	Polyester	BK on WT	1.000 (25.4)	25 ft. (7.6 m)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 2	M-89-422	B-422	Polyester	BK on WT	1.500 (38.1)	0.500 (12.7)	180	R6000
BMP41, 51, 53	Fig. 2	M-90-422	B-422	Polyester	BK on WT	1.500 (38.1)	0.750 (19.1)	180	R6000
B-428 Metallized Polyester Material									
BMP41, 51, 53	Fig. 2	M-47-428	B-428	Polyester	BK on Lt Gray	1.000 (25.4)	0.500 (12.7)	480	R4300
BMP41, 51, 53	Fig. 2	M-92-428-BB	B-428	Polyester	BK on Lt Gray	1.130 (28.7)	0.500 (12.7)	239	R4300
BMP41, 51, 53	Fig. 2	M-60-428	B-428	Polyester	BK on Lt Gray	2.000 (50.8)	1.000 (25.4)	140	R4300
B-483 Ultra-Aggressive Polyester									
BMP41, 51, 53	Fig. 2	M-60-483	B-483	Polyester	BK on WT	2.000 (50.8)	1.000 (25.4)	140	R6000
B-499 Nylon Cloth Material									
BMP41, 51, 53	Fig. 33	MC-375-499	B-499	Nylon Cloth	BK on WT	0.375 (9.5)	16 ft. (4.9 m)	1 roll (cont.)	R4300
BMP41, 51, 53	Fig. 33	MC-500-499	B-499	Nylon Cloth	BK on WT	0.500 (12.7)	16 ft. (4.9 m)	1 roll (cont.)	R4300
BMP41, 51, 53	Fig. 33	M-11-499	B-499	Nylon Cloth	BK on WT	0.750 (19.1)	0.500 (12.7)	1 roll (cont.)	R4300
BMP41, 51, 53	Fig. 33	MC-750-499	B-499	Nylon Cloth	BK on WT	0.750 (19.1)	16 ft. (4.9 m)	1 roll (cont.)	R4300
BMP41, 51, 53	Fig. 33	M-130-499	B-499	Nylon Cloth	BK on WT	0.825 (20.9)	0.375 (9.5)	1 roll (cont.)	R4300
BMP41, 51, 53	Fig. 33	M-84-499	B-499	Nylon Cloth	BK on WT	0.900 (22.8)	0.500 (12.7)	1 roll (cont.)	R4300
BMP41, 51, 53	Fig. 33	M-131-499	B-499	Nylon Cloth	BK on WT	1.000 (25.4)	0.500 (12.7)	1 roll (cont.)	R4300
BMP41, 51, 53	Fig. 33	M-128-499	B-499	Nylon Cloth	BK on WT	1.000 (25.4)	1.900 (48.3)	1 roll (cont.)	R4300
B-595 Indoor and Outdoor Vinyl Material									
BMP41, 51, 53	Fig. 33	MC-500-595-OR-BK	B-595	Vinyl	BK on OR*	0.500 (12.7)	25 ft. (7.6 m)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC-750-595-OR-BK	B-595	Vinyl	BK on OR*	0.750 (19.1)	25 ft. (7.6 m)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC1-1000-595-OR-BK	B-595	Vinyl	BK on OR*	1.000 (25.4)	25 ft. (7.6 m)	1 roll (cont.)	R6000

* For additional general purpose tapes, refer to the indoor and outdoor grade facility and safety labels on page 109.

BMP41 magnet accessory

The optional heavy-duty magnet accessory for BMP41 allows you to go hands free. Apply the magnet to the back of your printer and then stick it to a magnetized surface or wall.



Self-Laminating Vinyl Wire and Cable Labels (B-427)

Labels feature a clear, non-printable area that wraps around print-on area to protect text. Vinyl material offers superior resistance to handling, solvents, oil, grease, dirt and water. Temp. range -40° F to 158° F (-40° C to 70° C), UL recognized.




Figure 32




Figure 42b



Fits Printers	Figure	Catalog#	Color	Approx. Wire Gauge	Max Wire Dia. Inch (mm)	Label Width A Inch (mm)	Label Height B Inch (mm)	Print-On Height C Inch (mm)	Labels Per Roll	Sized To Fit	Ribbon in Cartridge
BMP41, 51, 53	Fig. 32	M-11-427	BK on WT	16 to 10	0.160 (4.1)	0.500 (12.7)	0.750 (19.1)	0.375 (9.5)	360	CAT-6, 4 pair UTP Copper	R4300
BMP41, 51, 53	Fig. 32	M-136-427	BK on WT	16 to 10	0.160 (4.1)	1.000 (25.4)	0.750 (19.1)	0.375 (9.5)	340	CAT-6, 4 pair UTP Copper	R4300
BMP41, 51, 53	Fig. 42b	MC-750-427	BK on WT	16 to 10	0.270 (6.7)	25 ft. (7.6 m)	0.750 (19.1)	0.375 (9.5)	1 roll (cont.)	CAT-6, 4 pair UTP Copper	R4300
BMP41, 51, 53	Fig. 32	M-47-427	BK on WT	12 to 10	0.210 (5.3)	1.000 (25.4)	0.500 (12.7)	0.375 (9.5)	360	2 pair Fiber/Coaxial, Single/Multi-Mode	R4300
BMP41, 51, 53	Fig. 32	M-48-427	BK on WT	12 to 10	0.210 (5.3)	0.750 (19.1)	1.000 (25.4)	0.375 (9.5)	200	CAT-6, 4 pair UTP Copper, Fiber, Coaxial	R4300
BMP41, 51, 53	Fig. 32	M-49-427	BK on WT	12 to 10	0.210 (5.3)	1.000 (25.4)	1.000 (25.4)	0.375 (9.5)	260	2 pair Fiber/Coaxial, Single/Multi-Mode	R4300
BMP41, 51, 53	Fig. 32	M-102-427	BK on WT	10 to 4	0.270 (6.7)	0.500 (12.7)	1.250 (31.7)	0.375 (9.5)	200	CAT-6, 4 pair UTP Copper	R4300
BMP41, 51, 53	Fig. 32	M-143-427	BK on WT	10 to 4	0.270 (6.7)	1.000 (25.4)	1.250 (31.7)	0.500 (12.7)	200	CAT-6, 4 pair UTP Copper, Fiber, Coaxial	R4300
BMP41, 51, 53	Fig. 32	M-89-427	BK on WT	10 to 4	0.320 (8.1)	0.500 (12.7)	1.500 (38.1)	0.500 (12.7)	180	CAT-6, 4 pair UTP Copper	R4300
BMP41, 51, 53	Fig. 32	M-90-427	BK on WT	10 to 4	0.320 (8.1)	0.750 (19.1)	1.500 (38.1)	0.500 (12.7)	180	CAT-6, 4 pair UTP Copper	R4300
BMP41, 51, 53	Fig. 32	M-91-427	BK on WT	10 to 4	0.320 (8.1)	1.000 (25.4)	1.500 (38.1)	0.500 (12.7)	180	CAT-6, 4 pair UTP Copper, Fiber, Coaxial	R4300
BMP41, 51, 53	Fig. 32	M-51-427	BK on WT	3 to 2/0	0.530 (13.5)	1.000 (25.4)	2.500 (63.5)	0.750 (19.1)	110	25 pair Copper, 4-12 pair Fiber, Coaxial	R4300
BMP41, 51, 53	Fig. 32	M-53-427	BK on WT	3/0 to 400 kcmil	0.850 (21.6)	1.000 (25.4)	4.000 (101.6)	1.000 (25.4)	70	50 pair Copper, 24 pair Fiber, Backbone	R4300
BMP41, 51, 53	Fig. 32	M-91-427-YL	BK on YL	10 to 4	0.320 (8.1)	1.000 (25.4)	1.500 (38.1)	0.500 (12.7)	180	CAT-6, 4 pair UTP Copper, Fiber, Coaxial	R4300
BMP41, 51, 53	Fig. 32	M-51-427-YL	BK on YL	3 to 2/0	0.530 (13.5)	1.000 (25.4)	2.500 (63.5)	0.750 (19.1)	110	25 pair Copper, 4-12 pair Fiber, Coaxial	R4300
BMP41, 51, 53	Fig. 32	M-53-427-YL	BK on YL	3/0 to 400 kcmil	0.850 (21.6)	1.000 (25.4)	4.000 (101.6)	1.000 (25.4)	70	50 pair Copper, 24 pair Fiber, Backbone	R4300

PermaSleeve® PS Polyolefin Wire Markers (B-342)

Military / industrial grade sleeves offer the ultimate in marker durability, permanence and aesthetic appearance. 3:1 heat-shrinkable markers fit snugly around wires, are fade-resistant and flame-retardant. Temp range: -67° F to 275° F (-55° C to 130° C). RoHS compliant and UL recognized.

Meets specifications:

- SSAE-AS-23053/5
- SAE-AS-81531

Tested per:

- ASTM E162
- ASTM E662
- MIL-STD-202




Figure 44




Figure 58



Fits Printers	Figure	Catalog #	B#	Color	Approx. Wire Gauge	Wire Diameter Range Inch (mm)	Supplied Diameter B Inch (mm)	Supplied Width A Inch (mm)	Sleeves Per Roll	Ribbon in Cartridge
BMP41, 51, 53	Fig. 44	* M-125-075-342	B-342	BK on WT	22 to 16	0.046 - 0.110 (1.2 - 2.8)	0.235 (5.9)	0.750 (19.1)	80	R4300
BMP41, 51, 53	Fig. 58	* MC-125-342	B-342	BK on WT	22 to 16	0.046 - 0.110 (1.2 - 2.8)	0.235 (5.9)	7 ft. (2.1 m)	1 roll (cont.)	R4300
BMP41, 51, 53	Fig. 44	* M-187-075-342	B-342	BK on WT	20 to 10	0.062 - 0.150 (1.6 - 3.8)	0.335 (8.5)	0.750 (19.1)	80	R4300
BMP41, 51, 53	Fig. 58	* MC-187-342	B-342	BK on WT	20 to 10	0.062 - 0.150 (1.6 - 3.8)	0.335 (8.5)	7 ft. (2.1 m)	1 roll (cont.)	R4300
BMP41, 51, 53	Fig. 44	* M-250-075-342	B-342	BK on WT	16 to 8	0.094 - 0.215 (2.4 - 5.5)	0.439 (11.1)	0.750 (19.1)	80	R4300
BMP41, 51, 53	Fig. 58	* MC-250-342	B-342	BK on WT	16 to 8	0.094 - 0.215 (2.4 - 5.5)	0.439 (11.1)	7 ft. (2.1 m)	1 roll (cont.)	R4300
BMP41, 51, 53	Fig. 44	* M-375-075-342	B-342	BK on WT	12 to 4	0.125 - 0.320 (3.2 - 8.1)	0.645 (16.4)	0.750 (19.1)	80	R4300
BMP41, 51, 53	Fig. 58	* MC-375-342	B-342	BK on WT	12 to 4	0.125 - 0.320 (3.2 - 8.1)	0.645 (16.4)	7 ft. (2.1 m)	1 roll (cont.)	R4300
BMP41, 51, 53	Fig. 58	* MC-125-342-YL	B-342	BK on YL	22 to 16	0.046 - 0.110 (1.2 - 2.8)	0.235 (5.9)	7 ft. (2.1 m)	1 roll (cont.)	R4300
BMP41, 51, 53	Fig. 58	* MC-187-342-YL	B-342	BK on YL	20 to 10	0.062 - 0.150 (1.6 - 3.8)	0.335 (8.5)	7 ft. (2.1 m)	1 roll (cont.)	R4300
BMP41, 51, 53	Fig. 58	* MC-250-342-YL	B-342	BK on YL	16 to 8	0.094 - 0.215 (2.4 - 5.5)	0.439 (11.1)	7 ft. (2.1 m)	1 roll (cont.)	R4300

Nylon Cloth Cable Flags (B-499)

Pre-formatted with two printable areas, allowing flag to be easily folded around wire to create a two-sided, printed flag. Nylon Cloth with permanent adhesive is pliable for rough or smooth surfaces. Temp. range: -94° F to 194° F (-70° C to 90° C). UL recognized.





Figure 63



Fits Printers	Figure	Catalog #	B#	Material	Color	Label Width A Inch (mm)	Label Height B Inch (mm)	Non-Print Area Inch (mm)	Labels Per Roll	Ribbon in Cartridge
BMP41, 51, 53	Fig. 63	M-141-499	B-499	Nylon Cloth	BK on WT	1.000 (25.4)	1.000 (25.4)	0.250 (6.3)	90	R4300

Repositionable Adhesive Vinyl Cloth Wire and Cable Labels (B-498)

Printer automatically repeats your text to fill the label for maximum readability. The adhesive and cloth backing offers excellent holding power, yet allow for clean removal and repositioning if necessary. Temp. range -40° F to 175° F (-40° C to 70° C). UL recognized.





Fits Printers	Figure	Catalog #	B#	Material	Color	Approx. Wire Gauge	Max. Wire Dia. Inch (mm)	Label Width A Inch (mm)	Label Height B Inch (mm)	Labels Per Roll	Ribbon in Cartridge
BMP41, 51, 53	Fig. 2	M-7-498	B-498	Vinyl	BK on WT	22 to 16	0.110 (2.8)	0.500 (12.7)	0.500 (12.7)	240	R6200
BMP41, 51, 53	Fig. 2	M-11-498	B-498	Vinyl	BK on WT	16 to 10	0.160 (4.1)	0.750 (19.1)	0.500 (12.7)	220	R6200
BMP41, 51, 53	Fig. 2	M-48-498	B-498	Vinyl	BK on WT	12 to 10	0.210 (5.3)	1.000 (25.4)	0.750 (19.1)	180	R6200
BMP41, 51, 53	Fig. 2	M-49-498	B-498	Vinyl	BK on WT	12 to 10	0.210 (5.3)	1.000 (25.4)	1.000 (25.4)	160	R6200
BMP41, 51, 53	Fig. 2	M-131-498	B-498	Vinyl	BK on WT	10 to 4	0.270 (6.7)	1.000 (25.4)	0.500 (12.7)	180	R6200
BMP41, 51, 53	Fig. 2	M-91-498	B-498	Vinyl	BK on WT	10 to 4	0.270 (6.7)	1.500 (38.1)	1.000 (25.4)	120	R6200

Patch Panel, Punch Block, Desi Strip and Faceplate Labels (B-412 and B-422)

Create a fully formatted serialized punch block label to fit your equipment or label your ports, jacks and outlets with adhesive labels or slide-in strips.


- **B-412 Polypropylene Tags:** Non-adhesive slide-in strips
- **B-422 Polyester Material:** Permanent adhesive, good for powder-coated/textured surfaces. Temp. range: -40° F to 212° F (-40° C to 100° C). UL recognized.



Fits Printers	Figure	Catalog #	B#	Material	Color	Label Width A Inch (mm)	Roll Length B Inch (mm)	Labels Per Roll	Ribbon in Cartridge
B-412 Non-Adhesive Polypropylene Tags									
BMP41, 51, 53	Fig. 33c	MC-375-412	B-412	Polypropylene	BK on WT	0.375 (9.5)	20 ft. (6.1 m)	1 roll (cont.)	R4300
BMP41, 51, 53	Fig. 33c	MC-475-412	B-412	Polypropylene	BK on WT	0.475 (12.1)	20 ft. (6.1 m)	1 roll (cont.)	R4300
BMP41, 51, 53	Fig. 33c	MC-625-412	B-412	Polypropylene	BK on WT	0.625 (15.8)	20 ft. (6.1 m)	1 roll (cont.)	R4300
B-422 Polyester Material									
BMP41, 51, 53	Fig. 33c	MC-375-422	B-422	Polyester	BK on WT	0.375 (9.5)	25 ft. (7.6 m)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33c	MC-475-422	B-422	Polyester	BK on WT	0.475 (12.1)	25 ft. (7.6 m)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 2	M-7-422	B-422	Polyester	BK on WT	0.500 (12.7)	0.500 (12.7)	280	R6000
BMP41, 51, 53	Fig. 2	M-89-422	B-422	Polyester	BK on WT	0.500 (12.7)	1.500 (38.1)	180	R6000
BMP41, 51, 53	Fig. 2	M-90-422	B-422	Polyester	BK on WT	0.750 (19.1)	1.500 (38.1)	180	R6000
BMP41, 51, 53	Fig. 2	M-47-422	B-422	Polyester	BK on WT	1.000 (25.4)	0.500 (12.7)	480	R6000

Terminal Block Repositionable Adhesive Strips (B-498)

When using terminal block mode, printer can serialize and pre-space to your special thin widths to fit terminal blocks. The adhesive and cloth backing offers excellent holding power, yet allow for clean removal and repositioning if necessary. Temp. range -40° F to 175° F (-40° C to 70° C). UL recognized.



Fits Printers	Figure	Catalog #	B#	Material	Color	Label Width A Inch (mm)	Roll Length B Feet (m)	Labels Per Roll	Ribbon in Cartridge
BMP41, 51, 53	Fig. 33c	MC-240-498	B-498	Vinyl	BK on WT	0.240 (6.1)	16 (4.9)	1 roll (cont.)	R6200
BMP41, 51, 53	Fig. 33c	MC-318-498	B-498	Vinyl	BK on WT	0.318 (8.1)	16 (4.9)	1 roll (cont.)	R6200
BMP41, 51, 53	Fig. 33c	MC-375-498	B-498	Vinyl	BK on WT	0.375 (9.5)	20 (6.1)	1 roll (cont.)	R6200



По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04 Ангарск (3955)60-70-56 Архангельск (8182)63-90-72 Астрахань (8512)99-46-04 Барнаул (3852)73-04-60 Белгород (4722)40-23-64 Благовещенск (4162)22-76-07 Брянск (4832)59-03-52 Владивосток (423)249-28-31 Владикавказ (8672)28-90-48 Владимир (4922)49-43-18 Волгоград (844)278-03-48 Вологда (8172)26-41-59 Воронеж (473)204-51-73 Екатеринбург (343)384-55-89	Иваново (4932)77-34-06 Ижевск (3412)26-03-58 Иркутск (395)279-98-46 Казань (843)206-01-48 Калининград (4012)72-03-81 Калуга (4842)92-23-67 Кемерово (3842)65-04-62 Киров (8332)68-02-04 Коломна (4966)23-41-49 Кострома (4942)77-07-48 Краснодар (861)203-40-90 Красноярск (391)204-63-61 Курск (4712)77-13-04 Курган (3522)50-90-47 Липецк (4742)52-20-81	Магнитогорск (3519)55-03-13 Москва (495)268-04-70 Мурманск (8152)59-64-93 Набережные Челны (8552)20-53-41 Новокузнецк (3843)20-46-81 Ноябрьск (3496)41-32-12 Новосибирск (383)227-86-73 Омск (3812)21-46-40 Орел (4862)44-53-42 Оренбург (3532)37-68-04 Пенза (8412)22-31-16 Петрозаводск (8142)55-98-37 Псков (8112)59-10-37 Пермь (342)205-81-47	Ростов-на-Дону (863)308-18-15 Рязань (4912)46-61-64 Самара (846)206-03-16 Санкт-Петербург (812)309-46-40 Саратов (845)249-38-78 Севастополь (8692)22-31-93 Саранск (8342)22-96-24 Симферополь (3652)67-13-56 Смоленск (4812)29-41-54 Сочи (862)225-72-31 Ставрополь (8652)20-65-13 Сургут (3462)77-98-35 Сыктывкар (8212)25-95-17 Тамбов (4752)50-40-97 Тверь (4822)63-31-35	Тольятти (8482)63-91-07 Томск (3822)98-41-53 Тула (4872)33-79-87 Тюмень (3452)66-21-18 Ульяновск (8422)24-23-59 Улан-Удэ (3012)59-97-51 Уфа (347)229-48-12 Хабаровск (4212)92-98-04 Чебоксары (8352)28-53-07 Челябинск (351)202-03-61 Череповец (8202)49-02-64 Чита (3022)38-34-83 Якутск (4112)23-90-97 Ярославль (4852)69-52-93
--	--	---	--	--

Россия +7(495)268-04-70	Казахстан +(727)345-47-04	Беларусь +(375)257-127-884	Узбекистан +998(71)205-18-59	Киргизия +996(312)96-26-47
-------------------------	---------------------------	----------------------------	------------------------------	----------------------------

эл.почта: byb@nt-rt.ru || сайт: <https://brady.nt-rt.ru/>