

Этикетки для принтера BMR51

Технические характеристики

По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +(727)345-47-04

Беларусь +(375)257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: byb@nt-rt.ru || сайт: <https://brady.nt-rt.ru/>

Indoor and Outdoor Vinyl for Safety, Facility and Lean 5S (B-595)

Continuous vinyl material is ideal for lean 5S labels, pipe markers, equipment and production area identification. These labels offer excellent resistance to oils, detergents, dirt, grime and many solvents. Permanent adhesive, very pliable, good for rough surfaces and outdoor use. 8-10 years average outdoor durability.* Temp. range: -40° F to 180° F (-40° C to 82° C). UL recognized.



Figure 33



Fits Printers	Figure	Catalog #	B#	Material	Color	Label Width A Inch (mm)	Roll Length B Feet (m)	Labels Per Roll	Ribbon in Cartridge
BMP51, 53	Fig. 33	MC-250-595-WT-BK	B-595	Vinyl	Black on White	0.250 (6.35)	25 (7.62)	1 roll (cont.)	R10000
BMP41, 51, 53	Fig. 33	MC-375-595-WT-BK	B-595	Vinyl	Black on White	0.375 (9.5)	25 (7.62)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC-500-595-WT-BK	B-595	Vinyl	Black on White	0.500 (12.70)	25 (7.62)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC-750-595-WT-BK	B-595	Vinyl	Black on White	0.750 (19.10)	25 (7.62)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC1-1000-595-WT-BK	B-595	Vinyl	Black on White	1.000 (25.40)	25 (7.62)	1 roll (cont.)	R6000
BMP51, 53	Fig. 33	MC-1500-595-WT-BK	B-595	Vinyl	Black on White	1.500 (38.10)	25 (7.62)	1 roll (cont.)	R6000
BMP51, 53	Fig. 33	MC-250-595-YL-BK	B-595	Vinyl	Black on Yellow	0.250 (6.35)	25 (7.62)	1 roll (cont.)	R10000
BMP41, 51, 53	Fig. 33	MC-375-595-YL-BK	B-595	Vinyl	Black on Yellow	0.375 (9.5)	25 (7.62)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC-500-595-YL-BK	B-595	Vinyl	Black on Yellow	0.500 (12.70)	25 (7.62)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC-750-595-YL-BK	B-595	Vinyl	Black on Yellow	0.750 (19.10)	25 (7.62)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC1-1000-595-YL-BK	B-595	Vinyl	Black on Yellow	1.000 (25.40)	25 (7.62)	1 roll (cont.)	R6000
BMP51, 53	Fig. 33	MC-1500-595-YL-BK	B-595	Vinyl	Black on Yellow	1.500 (38.10)	25 (7.62)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC-500-595-OR-BK	B-595	Vinyl	Black on Orange	0.500 (12.70)	25 (7.62)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC-750-595-OR-BK	B-595	Vinyl	Black on Orange	0.750 (19.10)	25 (7.62)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC1-1000-595-OR-BK	B-595	Vinyl	Black on Orange	1.000 (25.40)	25 (7.62)	1 roll (cont.)	R6000
BMP51, 53	Fig. 33	MC-1500-595-OR-BK	B-595	Vinyl	Black on Orange	1.500 (38.10)	25 (7.62)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC-500-595-BL-WT	B-595	Vinyl	White on Blue	0.500 (12.70)	25 (7.62)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC-750-595-BL-WT	B-595	Vinyl	White on Blue	0.750 (19.10)	25 (7.62)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC1-1000-595-BL-WT	B-595	Vinyl	White on Blue	1.000 (25.40)	25 (7.62)	1 roll (cont.)	R4400
BMP51, 53	Fig. 33	MC-1500-595-BL-WT	B-595	Vinyl	White on Blue	1.500 (38.10)	25 (7.62)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC-375-595-RD-WT	B-595	Vinyl	White on Red	0.375 (9.5)	25 (7.62)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC-500-595-RD-WT	B-595	Vinyl	White on Red	0.500 (12.70)	25 (7.62)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC-750-595-RD-WT	B-595	Vinyl	White on Red	0.750 (19.10)	25 (7.62)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC1-1000-595-RD-WT	B-595	Vinyl	White on Red	1.000 (25.40)	25 (7.62)	1 roll (cont.)	R4400
BMP51, 53	Fig. 33	MC-1500-595-RD-WT	B-595	Vinyl	White on Red	1.500 (38.10)	25 (7.62)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC-500-595-GN-WT	B-595	Vinyl	White on Green	0.500 (12.70)	25 (7.62)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC-750-595-GN-WT	B-595	Vinyl	White on Green	0.750 (19.10)	25 (7.62)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC1-1000-595-GN-WT	B-595	Vinyl	White on Green	1.000 (25.40)	25 (7.62)	1 roll (cont.)	R4400
BMP51, 53	Fig. 33	MC-1500-595-GN-WT	B-595	Vinyl	White on Green	1.500 (38.10)	25 (7.62)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC-500-595-WT-RD	B-595	Vinyl	Red on White	0.500 (12.70)	25 (7.62)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC-750-595-WT-RD	B-595	Vinyl	Red on White	0.750 (19.10)	25 (7.62)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC1-1000-595-WT-RD	B-595	Vinyl	Red on White	1.000 (25.40)	25 (7.62)	1 roll (cont.)	R4400
BMP51, 53	Fig. 33	MC-1500-595-WT-RD	B-595	Vinyl	Red on White	1.500 (38.10)	25 (7.62)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC-500-595-CL-BK	B-595	Vinyl	Black on Clear	0.500 (12.70)	25 (7.62)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC-750-595-CL-BK	B-595	Vinyl	Black on Clear	0.750 (19.10)	25 (7.62)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC1-1000-595-CL-BK	B-595	Vinyl	Black on Clear	1.000 (25.40)	25 (7.62)	1 roll (cont.)	R4400
BMP51, 53	Fig. 33	MC-1500-595-CL-BK	B-595	Vinyl	Black on Clear	1.500 (38.10)	25 (7.62)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC-500-595-CL-WT	B-595	Vinyl	White on Clear	0.500 (12.70)	25 (7.62)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC-750-595-CL-WT	B-595	Vinyl	White on Clear	0.750 (19.10)	25 (7.62)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC1-1000-595-CL-WT	B-595	Vinyl	White on Clear	1.000 (25.40)	25 (7.62)	1 roll (cont.)	R4400
BMP51, 53	Fig. 33	MC-1500-595-CL-WT	B-595	Vinyl	White on Clear	1.500 (38.10)	25 (7.62)	1 roll (cont.)	R4400

* Average expected outdoor life of product will depend on user definition of failure, climatic conditions, mounting techniques and material color. The 8-10 year outdoor durability applies to the vinyl label stock only; ribbon durability will vary.

Inside-Panel Component Labels for Electrical, Automation and Data Centers (B-422, B-428, B-483, B-499 and B-595)

Variety of durable materials ideal for marking backer boards, DIN rail, relays, PLCs, switches and solenoids. Create serial or rating plates with barcodes, graphics and more with a flexible high-tack adhesive for easy and long-lasting adhesion.

- **B-422 Polyester Material:** Permanent adhesive, good for powder-coated and textured surfaces. Best on flat surfaces. Temp. range: -40° F to 212° F (-40° C to 100° C). UL recognized.
- **B-428 Metalized Polyester Material:** Permanent adhesive, silver finish. Temp. range: -40° F to 176° F (-40° C to 80° C). UL recognized.
- **B-483 Polyester Material:** Permanent adhesive for powder-coated and textured surfaces. Best on flat surfaces Temp. range: -40° F to 248° F (-40° C to 120° C). UL recognized.
- **B-499 Nylon Cloth Material:** Permanent adhesive. Pliable for rough or smooth surfaces. Temp. range: -94° F to 194° F (-70° C to 90° C). UL recognized.
- **B-595 Indoor / Outdoor Vinyl Material:** Permanent adhesive, very pliable, good for rough surfaces and outdoor use, wide range of colors. Temp. range: -40° F to 180° F (-40° C to 82° C). UL recognized.




Figure 2



Figure 33




Figure 46
(with border)

Fits Printers	Figure	Catalog #	B#	Material	Color	Label Width A Inch (mm)	Label Height B Inch (mm)	Labels Per Roll	Ribbon in Cartridge
B-422 Gloss Polyester									
BMP41, 51, 53	Fig. 33	MC-375-422	B-422	Gloss Polyester	Black on White	0.375 (9.5)	25 ft. (7.6 m)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC-475-422	B-422	Gloss Polyester	Black on White	0.475 (12.1)	25 ft. (7.6 m)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC-500-422	B-422	Gloss Polyester	Black on White	0.500 (12.7)	25 ft. (7.6 m)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 2	M-7-422	B-422	Gloss Polyester	Black on White	0.500 (12.70)	0.500 (12.70)	280	R6000
BMP41, 51, 53	Fig. 2	M-89-422	B-422	Gloss Polyester	Black on White	0.500 (12.70)	1.500 (38.10)	360	R6000
BMP41, 51, 53	Fig. 2	M-47-422	B-422	Gloss Polyester	Black on White	1.000 (25.40)	0.500 (12.70)	360	R6000
BMP41, 51, 53	Fig. 2	M-49-422	B-422	Gloss Polyester	Black on White	1.000 (25.40)	1.000 (25.40)	200	R6000
BMP41, 51, 53	Fig. 33	MC1-1000-422	B-422	Gloss Polyester	Black on White	1.000 (25.40)	25 ft. (7.62 m)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 2	M-90-422	B-422	Gloss Polyester	Black on White	1.500 (38.10)	0.750 (19.05)	200	R6000
B-428 Metalized Polyester									
BMP51, 53	Fig. 2	M-29-428	B-428	Metalized Polyester	Light Gray	0.500 (12.70)	1.500 (38.10)	360	R4300
BMP51, 53	Fig. 2	M-30-428	B-428	Metalized Polyester	Light Gray	0.750 (19.05)	1.500 (38.10)	260	R4300
BMP41, 51, 53	Fig. 2	M-47-428	B-428	Metalized Polyester	Light Gray	1.000 (25.40)	0.500 (12.70)	360	R4300
BMP41, 51, 53	Fig. 46	M-92-428-BB	B-428	Metalized Polyester	Light Gray	1.130 (28.70)	0.500 (12.70)	360	R4300
BMP41, 51, 53	Fig. 2	M-60-428	B-428	Metalized Polyester	Light Gray	2.000 (50.80)	1.000 (25.40)	80	R4300
B-483 Ultra-Aggressive Polyester									
BMP41, 51, 53	Fig. 2	M-47-483	B-483	Polyester	Black on White	1.000 (25.4)	0.500 (12.7)	480	R6000
BMP41, 51, 53	Fig. 2	M-61-483	B-483	Polyester	Black on White	2.000 (50.80)	0.500 (12.70)	80	R6000
BMP41, 51, 53	Fig. 2	M-60-483	B-483	Polyester	Black on White	2.000 (50.80)	1.000 (25.40)	80	R6000
B-499 Nylon Cloth									
BMP41, 51, 53	Fig. 2	M-131-499	B-499	Nylon Cloth	Black on White	0.500 (12.7)	1.000 (25.40)	180	R4300
BMP41, 51, 53	Fig. 2	M-11-499	B-499	Nylon Cloth	Black on White	0.500 (12.70)	0.750 (19.05)	220	R4300
BMP41, 51, 53	Fig. 2	M-84-499	B-499	Nylon Cloth	Black on White	0.900 (22.86)	0.500 (12.70)	200	R4300
BMP41, 51, 53	Fig. 2	M-128-499	B-499	Nylon Cloth	Black on White	1.000 (25.40)	1.900 (48.3)	100	R4300
BMP51, 53	Fig. 2	M-132-499	B-499	Nylon Cloth	Black on White	1.500 (38.10)	1.250 (31.75)	160	R4300
B-595 Indoor / Outdoor Vinyl Tape*									
BMP41, 51, 53	Fig. 33	MC-500-595-WT-BK	B-595	Vinyl	Black on White	0.500 (12.70)	25 ft. (7.62 m)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC1-1000-595-WT-BK	B-595	Vinyl	Black on White	1.000 (25.40)	25 ft. (7.62 m)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC-500-595-YL-BK	B-595	Vinyl	Black on Yellow	0.500 (12.70)	25 ft. (7.62 m)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC1-1000-595-YL-BK	B-595	Vinyl	Black on Yellow	1.000 (25.40)	25 ft. (7.62 m)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC-500-595-OR-BK	B-595	Vinyl	Black on Orange	0.500 (12.70)	25 ft. (7.62 m)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC1-1000-595-OR-BK	B-595	Vinyl	Black on Orange	1.000 (25.40)	25 ft. (7.62 m)	1 roll (cont.)	R6000

* For additional vinyl label colors, refer to the B-595 indoor / outdoor grade facility and safety labels on page 116.

Self-Laminating Vinyl Wire and Cable Labels (B-427)

Labels feature a clear, non-printable area that wraps around print-on area to protect text. Vinyl material offers superior resistance to handling, solvents, oil, grease, dirt and water. Temp. range -40° F to 158° F (-40° C to 70° C), UL recognized.




Figure 2




Figure 42




Figure 42a
(continuous)




Figure 15c



Fits Printers	Figure	Catalog #	B#	Material	Color	Approx. Wire Gauge	Max. Wire Diameter Inch (mm)	Label Width A Inch (mm)	Label Height B Inch (mm)	Print-On Height C Inch (mm)	Labels Per Roll	Ribbon in Cartridge
B-427 Self-Laminating Vinyl												
BMP51, 53	Fig. 2	M-135-427-AW	B-427	Vinyl	BK on WT	All White	-	1.100 (27.9)	0.250 (6.35)	0.250 (6.35)	240	R4300
BMP41, 51, 53	Fig. 42	M-11-427	B-427	Vinyl	BK on WT	16 to 10	0.160 (4.06)	0.500 (12.70)	0.750 (19.05)	0.375 (9.53)	360	R4300
BMP41, 51, 53	Fig. 42	M-136-427	B-427	Vinyl	BK on WT	16 to 10	0.160 (4.06)	1.000 (25.40)	0.750 (19.05)	0.375 (9.53)	340	R4300
BMP41, 51, 53	Fig. 42	M-49-427	B-427	Vinyl	BK on WT	12 to 10	0.210 (5.33)	1.000 (25.40)	1.000 (25.40)	0.375 (9.53)	260	R4300
BMP51, 53	Fig. 42	M-133-427	B-427	Vinyl	BK on WT	12 to 10	0.210 (5.33)	1.750 (44.4)	1.000 (25.40)	0.375 (9.53)	140	R4300
BMP41, 51, 53	Fig. 42	M-102-427	B-427	Vinyl	BK on WT	10 to 4	0.270 (6.86)	0.500 (12.70)	1.250 (31.75)	0.375 (9.53)	200	R4300
BMP41, 51, 53	Fig. 42	M-143-427	B-427	Vinyl	BK on WT	10 to 4	0.270 (6.86)	1.000 (25.40)	1.250 (31.75)	0.500 (12.70)	200	R4300
BMP51, 53	Fig. 42	M-115-427	B-427	Vinyl	BK on WT	10 to 4	0.270 (6.86)	1.500 (38.10)	1.250 (31.75)	0.500 (12.70)	200	R4300
BMP41, 51, 53	Fig. 42	M-89-427	B-427	Vinyl	BK on WT	10 to 4	0.320 (8.13)	0.500 (12.70)	1.500 (38.10)	0.500 (12.70)	360	R4300
BMP41, 51, 53	Fig. 42	M-90-427	B-427	Vinyl	BK on WT	10 to 4	0.320 (8.13)	0.750 (19.05)	1.500 (38.10)	0.500 (12.70)	200	R4300
BMP41, 51, 53	Fig. 15c	M-47-427	B-427	Vinyl	BK on WT	12 to 10	0.210 (5.33)	1.000 (25.40)	0.500 (12.70)	0.375 (9.53)	360	R4300
BMP41, 51, 53	Fig. 15c	M-48-427	B-427	Vinyl	BK on WT	12 to 10	0.210 (5.33)	1.000 (25.40)	0.750 (19.05)	0.375 (9.53)	200	R4300
BMP41, 51, 53	Fig. 42	M-91-427	B-427	Vinyl	BK on WT	10 to 4	0.320 (8.13)	1.000 (25.40)	1.500 (38.10)	0.500 (12.70)	200	R4300
BMP51, 53	Fig. 42	M-32-427	B-427	Vinyl	BK on WT	10 to 4	0.320 (8.13)	1.500 (38.10)	1.500 (38.10)	0.500 (12.70)	180	R4300
BMP51, 53	Fig. 42	M-134-427	B-427	Vinyl	BK on WT	10 to 4	0.320 (8.13)	1.750 (44.4)	1.500 (38.10)	0.500 (12.70)	140	R4300
BMP41, 51, 53	Fig. 42	M-51-427	B-427	Vinyl	BK on WT	3 to 2/0	0.530 (13.46)	1.000 (25.40)	2.500 (63.50)	0.750 (19.05)	80	R4300
BMP51, 53	Fig. 42	M-116-427	B-427	Vinyl	BK on WT	3 to 2/0	0.530 (13.46)	1.500 (38.10)	2.500 (63.50)	0.750 (19.05)	80	R4300
BMP41, 51, 53	Fig. 42	M-53-427	B-427	Vinyl	BK on WT	3/0-400 kcmil	0.850 (21.59)	1.000 (25.40)	4.000 (101.6)	1.000 (25.40)	70	R4300
BMP51, 53	Fig. 42	M-33-427	B-427	Vinyl	BK on WT	3/0-400 kcmil	0.850 (21.59)	1.500 (38.10)	4.000 (101.6)	1.000 (25.40)	70	R4300
BMP51, 53	Fig. 42	M-34-427	B-427	Vinyl	BK on WT	3/0-400 kcmil	1.300 (33.02)	1.500 (38.10)	6.000 (152.40)	1.500 (38.10)	40	R4300
BMP41, 51, 53	Fig. 42	M-91-427-YL	B-427	Vinyl	BK on YL	10 to 4	0.320 (8.13)	1.000 (25.40)	1.500 (38.10)	0.500 (12.70)	200	R4300
BMP41, 51, 53	Fig. 42	M-51-427-YL	B-427	Vinyl	BK on YL	3 to 2/0	0.530 (13.46)	1.000 (25.40)	2.500 (63.50)	0.750 (19.05)	80	R4300
BMP41, 51, 53	Fig. 42	M-53-427-YL	B-427	Vinyl	BK on YL	3/0-400 kcmil	0.850 (21.59)	1.000 (25.40)	4.000 (101.6)	1.000 (25.40)	70	R4300
B-427 Continuous Self-Laminating Vinyl												
BMP41, 51, 53	Fig. 42a	MC-750-427	B-427	Vinyl	BK on WT	16 to 10	0.270 (6.86)	25 ft. (7.62 m)	0.750 (19.05)	0.375 (9.53)	1 roll (cont.)	R4300
BMP51, 53	Fig. 42a	MC-1000-427	B-427	Vinyl	BK on WT	12 to 10	0.850 (21.59)	25 ft. (7.62 m)	1.000 (25.40)	0.375 (9.53)	1 roll (cont.)	R4300
BMP51, 53	Fig. 42a	MC-1250-427	B-427	Vinyl	BK on WT	10 to 4	0.530 (13.46)	25 ft. (7.62 m)	1.250 (31.75)	0.500 (12.70)	1 roll (cont.)	R4300
BMP51, 53	Fig. 42a	MC-1500-427	B-427	Vinyl	BK on WT	10 to 4	0.270 (6.86)	25 ft. (7.62 m)	1.500 (38.10)	0.500 (12.70)	1 roll (cont.)	R4300

Repositionable Adhesive Vinyl Cloth Wire and Cable Labels (B-498)

Printer automatically repeats your text to fill the label for maximum readability. The adhesive and cloth backing offer excellent holding power, yet allow for clean removal and repositioning if necessary. Temp. range -40° F to 175° F (-40° C to 70° C). UL recognized.




Figure 2



Fits Printers	Figure	Catalog #	B#	Material	Color	Approx. Wire Gauge	Max. Wire Dia. Inch (mm)	Label Width A Inch (mm)	Label Height B Inch (mm)	Labels Per Roll	Ribbon in Cartridge
BMP41, 51, 53	Fig. 2	M-7-498	B-498	Vinyl Cloth	BK on WT	22 to 16	0.110 (2.80)	0.500 (12.70)	0.500 (12.70)	240	R6200
BMP41, 51, 53	Fig. 2	M-11-498	B-498	Vinyl Cloth	BK on WT	16 to 10	0.160 (4.00)	0.750 (19.05)	0.500 (12.70)	220	R6200
BMP41, 51, 53	Fig. 2	M-131-498	B-498	Vinyl Cloth	BK on WT	12 to 10	0.210 (5.00)	0.500 (12.70)	1.000 (25.40)	180	R6200
BMP41, 51, 53	Fig. 2	M-48-498	B-498	Vinyl Cloth	BK on WT	12 to 10	0.210 (5.00)	0.750 (19.05)	1.000 (25.40)	180	R6200
BMP41, 51, 53	Fig. 2	M-163-498	B-498	Vinyl Cloth	BK on WT	12 to 10	0.210 (5.00)	1.000 (25.40)	0.500 (12.70)	180	R6200
BMP41, 51, 53	Fig. 2	M-49-498	B-498	Vinyl Cloth	BK on WT	12 to 10	0.210 (5.00)	1.000 (25.40)	1.000 (25.40)	160	R6200
BMP51, 53	Fig. 2	M-103-498	B-498	Vinyl Cloth	BK on WT	10 to 4	0.270 (7.00)	1.000 (25.40)	1.250 (31.75)	160	R6200
BMP41, 51, 53	Fig. 2	M-91-498	B-498	Vinyl Cloth	BK on WT	10 to 4	0.270 (7.00)	1.000 (25.40)	1.500 (38.10)	160	R6200
BMP51, 53	Fig. 2	M-128-498	B-498	Vinyl Cloth	BK on WT	10 to 4	0.270 (7.00)	1.000 (25.40)	1.900 (48.3)	100	R6200

PermaSleeve® PS Polyolefin Wire Markers (B-342)

Military / industrial grade sleeves offer the ultimate in marker durability, permanence and aesthetic appearance. 3:1 heat-shrinkable markers fit snugly around wires, are fade-resistant and flame-retardant. Temp range: -67° F to 275° F (-55° C to 130° C). RoHS compliant and UL recognized.

Meets specifications:

- SSAE-AS-23053/5
- SAE-AS-81531

Tested per:

- ASTM E162
- ASTM E662
- MIL-STD-202




Figure 44




Figure 58



Fits Printers	Figure	Catalog #	B#	Color	Approx. Wire Gauge	For Wire Diameter Inch (mm) Min. Max	Sleeve Width A Inch (mm)	Supplied Diameter B Inch (mm)	Sleeves Per Roll	Ribbon in Cartridge
B-342 Die-Cut Sleeve										
BMP41, 51, 53	Fig. 44	* M-125-075-342	B-342	BK on WT	22 to 16	0.046 - 0.110 (1.20 - 2.80)	0.750 (19.1)	0.235 (5.97)	80	R4300
BMP51, 53	Fig. 44	* M-125-1-342	B-342	BK on WT	22 to 16	0.046 - 0.110 (1.20 - 2.80)	1.000 (25.40)	0.235 (5.97)	80	R4300
BMP41, 51, 53	Fig. 44	* M-187-075-342	B-342	BK on WT	20 to 10	0.062 - 0.150 (1.60 - 3.80)	0.750 (19.1)	0.335 (8.51)	80	R4300
BMP51, 53	Fig. 44	* M-187-1-342	B-342	BK on WT	20 to 10	0.062 - 0.150 (1.60 - 3.80)	1.000 (25.40)	0.335 (8.51)	80	R4300
BMP41, 51, 53	Fig. 44	* M-250-075-342	B-342	BK on WT	16 to 8	0.094 - 0.215 (2.40 - 5.50)	0.750 (19.1)	0.439 (11.15)	80	R4300
BMP51, 53	Fig. 44	* M-250-1-342	B-342	BK on WT	16 to 8	0.094 - 0.215 (2.40 - 5.50)	1.000 (25.40)	0.439 (11.15)	80	R4300
BMP41, 51, 53	Fig. 44	* M-375-075-342	B-342	BK on WT	12 to 4	0.125 - 0.320 (3.20 - 8.10)	0.750 (19.1)	0.645 (16.38)	80	R4300
BMP51, 53	Fig. 44	* M-375-1-342	B-342	BK on WT	12 to 4	0.125 - 0.320 (3.20 - 8.10)	1.000 (25.40)	0.645 (16.38)	80	R4300
B-342 Continuous Sleeving										
BMP41, 51, 53	Fig. 58	* MC-125-342	B-342	BK on WT	22 to 16	0.046 - 0.110 (1.20 - 2.80)	7 ft. (2.13 m)	0.235 (5.97)	1 roll (cont.)	R4300
BMP41, 51, 53	Fig. 58	* MC-187-342	B-342	BK on WT	20 to 10	0.062 - 0.150 (1.60 - 3.80)	7 ft. (2.13 m)	0.335 (8.51)	1 roll (cont.)	R4300
BMP41, 51, 53	Fig. 58	* MC-250-342	B-342	BK on WT	16 to 8	0.094 - 0.215 (2.40 - 5.50)	7 ft. (2.13 m)	0.439 (11.15)	1 roll (cont.)	R4300
BMP41, 51, 53	Fig. 58	* MC1-375-342	B-342	BK on WT	12 to 4	0.125 - 0.320 (3.20 - 8.10)	7 ft. (2.13 m)	0.645 (16.38)	1 roll (cont.)	R4300
BMP41, 51, 53	Fig. 58	* MC-125-342-YL	B-342	BK on YL	22 to 16	0.046 - 0.110 (1.20 - 2.80)	7 ft. (2.13 m)	0.235 (5.97)	1 roll (cont.)	R4300
BMP41, 51, 53	Fig. 58	* MC-187-342-YL	B-342	BK on YL	20 to 10	0.062 - 0.150 (1.60 - 3.80)	7 ft. (2.13 m)	0.335 (8.51)	1 roll (cont.)	R4300
BMP41, 51, 53	Fig. 58	* MC-250-342-YL	B-342	BK on YL	16 to 8	0.094 - 0.215 (2.40 - 5.50)	7 ft. (2.13 m)	0.439 (11.15)	1 roll (cont.)	R4300

Wire and Cable Flags and Tags (B-109, B-145, B-425 and B-499)

Allow more legible information on data cables and smaller diameter wires. Permits you to handle and view labels without touching the wires.

- **B-109 Non-Adhesive Polyethylene Tags:** Multi-purpose tags for identifying multi-conductor cables. Good weatherability and legibility after solvent exposure.
- **B-145 Polyethylene Tag Material:** Multi-purpose matte material for tag applications. Ideal for identifying multi-conductor cable, inventory, equipment, lockout, safety warning repair and work-in progress.
- **B-425 Polypropylene Solvent Resistant Material:** Matte white polypropylene with excellent solvent resistance and print performance; not recommended for long-term outdoor use.
- **B-499 Nylon Cloth Material:** Permanent adhesive. Pliable for rough or smooth surfaces. Temp. range: -94° F to 194° F (-70° C to 90° C). UL recognized.




Figure 48




Figure 50




Figure 57




Figure 63


Fits Printers	Figure	Catalog #	B#	Material	Color	Label Width A Inch (mm)	Label Height B Inch (mm)	Label Height C Inch (mm)	Labels Per Roll	Ribbon in Cartridge
B-109 Polyethylene Tag										
BMP51, 53	Fig. 57	M-12-109	B-109	Polypropylene Tag	Black on White	3.000 (76.2)	0.750 (19.05)	-	80	R4300
B-145 Polypropylene Tag										
BMP51, 53	Fig. 50	M-111-145FR-GY	B-145	Polyethylene Tag	Black on Gray	1.206 (30.63)	0.750 (19.05)	-	80	R6000
B-425 Polypropylene Flag										
BMP51, 53	Fig. 48	MFT-01-425	B-425	Polypropylene Flag	Black on White	0.788 (20.01)	1.18 (29.97)	-	200	R4300
B-499 Nylon Cloth										
BMP41, 51, 53	Fig. 63	M-141-499	B-499	Nylon Cloth	Black on White	1.000 (25.40)	1.000 (25.40)	0.250 (6.35)	90	R4300
BMP51, 53	Fig. 63	M-152-499	B-499	Nylon Cloth	Black on White	1.500 (38.10)	0.500 (12.70)	0.250 (6.35)	160	R4300

Terminal Block Repositionable Adhesive Strips (B-498)

When using terminal block mode, printer can serialize and pre-space to your special thin widths to fit terminal blocks. The adhesive and cloth backing offers excellent holding power, yet allow for clean removal and repositioning if necessary. Temp. range -40° F to 175° F (-40° C to 70° C). UL recognized.



Figure 33



Fits Printers	Figure	Catalog #	B#	Material	Color	Label Width A Inch (mm)	Roll Length B Foot (m)	Labels Per Roll	Ribbon in Cartridge
BMP41, 51, 53	Fig. 33	MC-240-498	B-498	Vinyl Cloth	Black on White	0.240 (6.09)	16 (4.87)	1 roll (cont.)	R6200
BMP41, 51, 53	Fig. 33	MC-318-498	B-498	Vinyl Cloth	Black on White	0.318 (8.07)	16 (4.87)	1 roll (cont.)	R6200
BMP41, 51, 53	Fig. 33	MC-375-498	B-498	Vinyl Cloth	Black on White	0.375 (9.52)	20 (6.1)	1 roll (cont.)	R6200

Patch Panel, Punch Block, Desi Strip and Faceplate Labels (B-412, B-422 and B-483)

Create a fully formatted serialized punch block label to fit your equipment or label your ports, jacks and outlets with adhesive labels or slide-in strips.

- **B-412 Polypropylene Tags:** Non-adhesive slide-in strips.
- **B-422 Polyester Material:** Permanent adhesive, good for powder-coated and textured surfaces. Temp. range: -40° F to 212° F (-40° C to 100° C). UL recognized.
- **B-483 Polyester Material:** Permanent adhesive for powder-coated and textured surfaces. Best on flat surfaces. Temp. range: -40° F to 248° F (-40° C to 120° C). UL recognized.





Figure 2



Figure 33



Fits Printers	Figure	Catalog #	B#	Material	Color	Label Width A Inch (mm)	Label Height B Inch (mm)	Labels Per Roll	Material Notes	Ribbon in Cartridge
B-412 Polypropylene Tag										
BMP41, 51, 53	Fig. 33	MC-375-412	B-412	Tag	Black on white	0.375 (9.53)	20 ft. (6.09 m)	1 roll (cont.)	Non-adhesive slide-in strips	R4300
BMP41, 51, 53	Fig. 33	MC-475-412	B-412	Tag	Black on white	0.475 (12.07)	20 ft. (6.09 m)	1 roll (cont.)	Non-adhesive slide-in strips	R4300
BMP41, 51, 53	Fig. 33	MC-625-412	B-412	Tag	Black on white	0.675 (12.07)	20 ft. (6.09 m)	1 roll (cont.)	Non-adhesive slide-in strips	R4300
B-422 Gloss Polyester										
BMP41, 51, 53	Fig. 33	MC-375-422	B-422	Polyester	Black on white	0.375 (9.5)	25 ft. (7.6 m)	1 roll (cont.)	Adhesive strips	R6000
BMP41, 51, 53	Fig. 33	MC-475-422	B-422	Polyester	Black on white	0.475 (12.1)	25 ft. (7.6 m)	1 roll (cont.)	Adhesive strips	R6000
BMP41, 51, 53	Fig. 33	MC-625-422	B-422	Polyester	Black on white	0.675 (12.07)	25 ft. (7.62 m)	1 roll (cont.)	Adhesive strips	R6000
BMP41, 51, 53	Fig. 2	M-7-422	B-422	Polyester	Black on white	0.500 (12.70)	0.500 (12.70)	280	Individual adhesive port labels	R6000
BMP41, 51, 53	Fig. 2	M-89-422	B-422	Polyester	Black on white	0.500 (12.70)	1.500 (38.10)	360	Individual adhesive labels	R6000
BMP41, 51, 53	Fig. 2	M-47-422	B-422	Polyester	Black on white	1.000 (25.40)	0.500 (12.70)	360	Individual adhesive labels	R6000
BMP41, 51, 53	Fig. 2	M-90-422	B-422	Polyester	Black on white	1.500 (38.10)	0.750 (19.05)	200	Individual adhesive labels	R6000
B-483 Ultra-Aggressive Polyester										
BMP41, 51, 53	Fig. 2	M-61-483	B-483	Polyester	Black on white	2.000 (50.80)	0.500 (12.70)	80	Individual adhesive labels	R6000

BMP51 cartridges

The necessary print ribbons for the BMP51 Label Printer are self-contained within the label roll cartridge.

No need to order or load separate print ribbons.



Polyester Labels for Rating Plates and General ID (B-422, B-428, B-432 and B-483)

Standard and metallized labels ideal for labeling rating plates, products and general industrial applications.

- **B-422 Polyester Material:** Permanent adhesive, good for powder-coated and textured surfaces. Best on flat surfaces. Temp. range: -40° F to 212° F (-40° C to 100° C). UL recognized.
- **B-428 Metallized Polyester Material:** Permanent adhesive, silver finish. Temp. range: -40° F to 176° F (-40° C to 80° C). UL recognized.
- **B-432 Polyester Material:** Durable glossy white polyester with permanent acrylic adhesive. Labels are chemical, oil and water resistant. Temp. range: -40° F to 212° F (-40° C to 100° C). UL recognized.
- **B-483 Polyester Material:** Permanent adhesive for powder-coated and textured surfaces. Best on flat surfaces Temp. range: -40° F to 248° F (-40° C to 120° C). UL recognized.




Figure 2



Figure 33



Figure 46 (with border)

Fits Printers	Figure	Catalog #	B#	Material	Color	Label Width A Inch (mm)	Label Height B Inch (mm)	Labels Per Roll	Ribbon in Cartridge
B-422 Gloss Polyester									
BMP41, 51, 53	Fig. 33	MC-375-422	B-422	Gloss Polyester	Black on White	0.375 (9.5)	25 ft. (7.6 m)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC-475-422	B-422	Gloss Polyester	Black on White	0.475 (12.1)	25 ft. (7.6 m)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 2	M-7-422	B-422	Gloss Polyester	Black on White	0.500 (12.70)	0.500 (12.70)	280	R6000
BMP41, 51, 53	Fig. 2	M-89-422	B-422	Gloss Polyester	Black on White	0.500 (12.70)	1.500 (38.10)	360	R6000
BMP41, 51, 53	Fig. 33	MC-500-422	B-422	Gloss Polyester	Black on White	0.500 (12.7)	25 ft. (7.6 m)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 2	M-47-422	B-422	Gloss Polyester	Black on White	1.000 (25.40)	0.500 (12.70)	360	R6000
BMP41, 51, 53	Fig. 2	M-49-422	B-422	Gloss Polyester	Black on White	1.000 (25.40)	1.000 (25.40)	200	R6000
BMP41, 51, 53	Fig. 33	MC1-1000-422	B-422	Gloss Polyester	Black on White	1.000 (25.40)	25ft. (7.62m)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 2	M-90-422	B-422	Gloss Polyester	Black on White	1.500 (38.10)	0.750 (19.05)	200	R6000
B-428 Metallized Polyester									
BMP51, 53	Fig. 2	M-29-428	B-428	Metallized Polyester	Light Gray	0.500 (12.70)	1.500 (38.10)	360	R4300
BMP51, 53	Fig. 2	M-30-428	B-428	Metallized Polyester	Light Gray	0.750 (19.05)	1.500 (38.10)	260	R4300
BMP41, 51, 53	Fig. 46	M-92-428-BB	B-428	Metallized Polyester	Light Gray	1.130 (28.70)	0.500 (12.70)	360	R4300
BMP41, 51, 53	Fig. 2	M-60-428	B-428	Metallized Polyester	Light Gray	2.000 (50.80)	1.000 (25.40)	80	R4300
B-432 Gloss Polyester									
BMP51, 53	Fig. 2	M-17-432-CL-BK	B-432	Gloss Polyester	Black on Clear	1.000 (25.40)	0.500 (12.70)	280	R6000
BMP51, 53	Fig. 2	M-78-432-CL-BK	B-432	Gloss Polyester	Black on Clear	1.900 (48.3)	1.000 (25.40)	100	R6000
B-483 Ultra-Aggressive Polyester									
BMP41, 51, 53	Fig. 2	M-47-483	B-483	Polyester	Black on White	1.000 (25.4)	0.500 (12.7)	360	R6000
BMP41, 51, 53	Fig. 2	M-61-483	B-483	Polyester	Black on White	2.000 (50.80)	0.500 (12.70)	80	R6000
BMP41, 51, 53	Fig. 2	M-60-483	B-483	Polyester	Black on White	2.000 (50.80)	1.000 (25.40)	80	R6000

Reflective Labels (B-584)

Reflective material shines back brightly when struck by light, making it ideal for labeling outdoor utility poles, hard hats, jobsite equipment and roof-top equipment. Meets Federal Spec L-S-300 for reflectivity. Average outdoor durability is 4-6 years. Temp. range: -40° F to 158° F (-40° C to 70° C).




Figure 33



Fits Printers	Figure	Catalog #	B#	Material	Color	Label Width A Inch (mm)	Roll Length B Feet (m)	Labels Per Roll	Ribbon in Cartridge
BMP41, 51, 53	Fig.33	MC-500-584	B-584	Reflective Tape	Black on White	0.500 (12.70)	25 (7.62)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig.33	MC-750-584	B-584	Reflective Tape	Black on White	0.750 (19.05)	25 (7.62)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig.33	MC-1000-584	B-584	Reflective Tape	Black on White	1.000 (25.40)	25 (7.62)	1 roll (cont.)	R6000
BMP51, 53	Fig.33	MC-1500-584	B-584	Reflective Tape	Black on White	1.500 (38.10)	25 (7.62)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig.33	MC-500-584-YL	B-584	Reflective Tape	Black on Yellow	0.500 (12.70)	25 (7.62)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig.33	MC-750-584-YL	B-584	Reflective Tape	Black on Yellow	0.750 (19.05)	25 (7.62)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig.33	MC-1000-584-YL	B-584	Reflective Tape	Black on Yellow	1.000 (25.40)	25 (7.62)	1 roll (cont.)	R6000
BMP51, 53	Fig.33	MC-1500-584-YL	B-584	Reflective Tape	Black on Yellow	1.500 (38.10)	25 (7.62)	1 roll (cont.)	R6000

Bin, Storage and General Industrial Labels (B-483, B-499 and B-595)

Several materials with an aggressive adhesive for use in commercial and industrial applications.

- **B-483 Polyester Material:** Permanent adhesive for powder-coated and textured surfaces. Best on flat surfaces Temp. range: -40° F to 248° F (-40° C to 120° C). UL recognized.
- **B-499 Nylon Cloth Material:** Permanent adhesive. Pliable for rough or smooth surfaces. Temp. range: -94° F to 194° F (-70° C to 90° C). UL recognized.
- **B-595 Indoor / Outdoor Vinyl Material:** Permanent adhesive, very pliable, good for rough surfaces and outdoor use. Temp. range: -40° F to 180° F (-40° C to 82° C). UL recognized.




Figure 2



Figure 3

Fits Printers	Figure	Catalog #	B#	Material	Color	Label Width A Inch (mm)	Label Height B Inch (mm)	Labels Per Roll	Ribbon in Cartridge
B-483 Ultra-Aggressive Polyester									
BMP41, 51, 53	Fig. 2	M-47-483	B-483	Polyester	Black on White	1.000 (25.4)	0.500 (12.7)	360	R6000
BMP41, 51, 53	Fig. 2	M-61-483	B-483	Polyester	Black on White	2.000 (50.80)	0.500 (12.70)	80	R6000
BMP41, 51, 53	Fig. 2	M-60-483	B-483	Polyester	Black on White	2.000 (50.80)	1.000 (25.40)	80	R6000
B-499 Nylon Cloth									
BMP41, 51, 53	Fig. 2	M-11-499	B-499	Nylon Cloth	Black on White	0.500 (12.70)	0.750 (19.05)	220	R4300
BMP41, 51, 53	Fig. 2	M-84-499	B-499	Nylon Cloth	Black on White	0.900 (22.86)	0.500 (12.70)	200	R4300
BMP41, 51, 53	Fig. 2	M-128-499	B-499	Nylon Cloth	Black on White	1.000 (25.40)	1.900 (48.3)	100	R4300
BMP51, 53	Fig. 2	M-132-499	B-499	Nylon Cloth	Black on White	1.500 (38.10)	1.250 (31.75)	160	R4300
B-595 Indoor / Outdoor Vinyl Tape*									
BMP41, 51, 53	Fig. 33	MC-750-595-WT-BK	B-595	Vinyl	Black on White	0.750 (19.10)	25 ft. (7.62 m)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC1-1000-595-WT-BK	B-595	Vinyl	Black on White	1.000 (25.40)	25 ft. (7.62 m)	1 roll (cont.)	R6000
BMP51, 53	Fig. 33	MC-1500-595-WT-BK	B-595	Vinyl	Black on White	1.500 (38.10)	25 ft. (7.62 m)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC-750-595-YL-BK	B-595	Vinyl	Black on Yellow	0.750 (19.10)	25 ft. (7.62 m)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC1-1000-595-YL-BK	B-595	Vinyl	Black on Yellow	1.000 (25.40)	25 ft. (7.62 m)	1 roll (cont.)	R6000
BMP51, 53	Fig. 33	MC-1500-595-YL-BK	B-595	Vinyl	Black on Yellow	1.500 (38.10)	25 ft. (7.62 m)	1 roll (cont.)	R6000

* For additional vinyl label colors, refer to the B-595 indoor / outdoor grade facility and safety labels on page 116.

Tamper-Indicating Vinyl Labels (B-351)

Destructible vinyl material prohibits one piece removal of label to indicate if the label has been tampered with.




Figure 2



Fits Printers	Figure	Catalog #	B#	Material	Color	Label Width A Inch (mm)	Label Height B Inch (mm)	Labels Per Roll	Ribbon in Cartridge
BMP51, 53	Fig. 2	M-17-351	B-351	Vinyl	Black on White	0.500 (12.70)	1.000 (25.40)	360	R6000
BMP51, 53	Fig. 2	M-20-351	B-351	Vinyl	Black on White	2.000 (50.80)	1.000 (25.40)	160	R6000

Water Dissolvable Paper Labels (B-403)

Paper material completely dissolves in warm water within 30 seconds, leaving no adhesive residue.




Figure 33



Fits Printers	Figure	Catalog #	B#	Material	Color	Label Width A Inch (mm)	Roll Length B Feet (m)	Labels Per Roll	Rec. Ribbon
BMP51, 53	Fig. 33	MC-750-403	B-403	Dissolvable Paper	Black on White	0.750 (19.05)	25 (7.62)	1 roll (cont.)	R4300
BMP51, 53	Fig. 33	MC-1500-403	B-403	Dissolvable Paper	Black on White	1.500 (38.1)	25 (7.62)	1 roll (cont.)	R4300

Cryogenic Tube, Vial and Cane Labels (B-461, B-490 and B-492)

FreezerBondz™ labels can be applied to room temperature or already frozen samples, with a small overlap. The label remains legible and will stick to the tube during processing, even when immersed in liquid- or vapor-phase nitrogen or placed in ultra-low temperature freezer storage.

- **B-461 Self-Laminating Polyester Material:** Ultra-thin polyester label with clear overlaminate tail that protects print and allows liquid levels to be visible.
- **B-490 Polyester Material:** White FreezerBondz label ideal for flat, frozen surfaces. Adheres to frozen tubes and vials when wrapped around itself by at least 0.125 inch.
- **B-492 Polyester Material:** FreezerBondz ultra-thin white polyester label for labeling of frosted/frozen or room temperature vials, tubes and canes. Superior chemical and abrasion resistance.




Figure 2




Figure 24




Figure 26




Figure 27



Figure 33




Figure 66

Fits Printers	Figure	Catalog #	B#	Material	Color	Label Width A Inch (mm)	Label Height B Inch (mm)	Print-On Height C Inch (mm)	Labels Per Roll	Ribbon in Cartridge
B-461 Self-Laminating Polyester										
BMP51, 53	Fig. 27	M-123-461	B-461	Self-Lam Polyester	Black on White	1.125 (28.5)	0.375 (9.5)	0.750 (19.0)	360	R4300
BMP51, 53	Fig. 27	M-122-461	B-461	Self-Lam Polyester	Black on White	1.125 (28.5)	0.500 (12.7)	0.750 (19.0)	360	R4300
BMP51, 53	Fig. 27	M-124-461	B-461	Self-Lam Polyester	Black on White	1.650 (41.9)	0.500 (12.7)	0.750 (19.0)	180	R4300
BMP41, 51, 53	Fig. 27	M-72-461	B-461	Self-Lam Polyester	Black on White	1.750 (44.4)	0.500 (12.7)	0.750 (19.0)	180	R4300
BMP51, 53	Fig. 27	M-74-461	B-461	Self-Lam Polyester	Black on White	2.200 (55.8)	0.500 (12.7)	0.750 (19.0)	140	R4300
BMP51, 53	Fig. 27	M-125-461	B-461	Self-Lam Polyester	Black on White	1.750 (44.4)	1.000 (25.4)	1.000 (25.4)	180	R4300
BMP51, 53	Fig. 27	M-126-461	B-461	Self-Lam Polyester	Black on White	1.800 (45.7)	0.600 (45.7)	1.000 (25.4)	180	R4300
BMP51, 53	Fig. 27	M-126-461	B-461	Self-Lam Polyester	Black on White	1.800 (45.7)	0.600 (45.7)	1.000 (25.4)	180	R4300
BMP51, 53	Fig. 27	M-75-461	B-461	Self-Lam Polyester	Black on White	2.625 (66.6)	0.375 (9.5)	1.000 (25.4)	120	R4300
BMP51, 53	Fig. 27	M-86-461	B-461	Self-Lam Polyester	Black on White	2.625 (66.6)	0.600 (45.7)	1.000 (25.4)	120	R4300
BMP51, 53	Fig. 27	M-129-461	B-461	Self-Lam Polyester	Black on White	2.250 (57.1)	1.500 (38.1)	1.250 (31.7)	140	R4300
BMP51, 53	Fig. 27	M-119-461	B-461	Self-Lam Polyester	Black on White	3.750 (95.3)	1.500 (38.1)	1.250 (31.7)	80	R4300
BMP51, 53	Fig. 33	MC-375-461	B-461	Self-Lam Polyester	Black on White	0.375 (9.5)	25 ft. (7.62 m)	-	1 roll (cont.)	R4300
BMP51, 53	Fig. 33	MC-500-461	B-461	Self-Lam Polyester	Black on White	0.500 (12.7)	25 ft. (7.6 m)	-	1 roll (cont.)	R4300
BMP51, 53	Fig. 33	MC-1000-461	B-461	Self-Lam Polyester	Black on White	1.000 (25.4)	25 ft. (7.6 m)	-	1 roll (cont.)	R4300
BMP51, 53	Fig. 33	MC-1250-461	B-461	Self-Lam Polyester	Black on White	1.250 (31.7)	25 ft. (7.6 m)	-	1 roll (cont.)	R4300
B-490 FreezerBondz Polyester										
BMP51, 53	Fig. 2	M-114-490	B-490	Polyester	Black on White	0.500 (12.7)	3.750 (9.2)	-	80	R4300
BMP51, 53	Fig. 2	M-112-490	B-490	Polyester	Black on White	1.250 (31.7)	0.375 (9.5)	-	360	R4300
BMP51, 53	Fig. 2	M-112-490	B-490	Polyester	Black on White	1.250 (31.7)	0.375 (9.5)	-	360	R4300
BMP51, 53	Fig. 2	M-113-490	B-490	Polyester	Black on White	1.500 (38.1)	2.200 (55.9)	-	140	R4300
BMP51, 53	Fig. 2	M-124-490	B-490	Polyester	Black on White	1.650 (41.9)	0.500 (12.7)	-	180	R4300
BMP51, 53	Fig. 2	M-125-490	B-490	Polyester	Black on White	1.750 (44.4)	1.000 (25.4)	-	180	R4300
BMP51, 53	Fig. 2	M-126-490	B-490	Polyester	Black on White	1.800 (45.7)	0.600 (45.7)	-	180	R4300
BMP51, 53	Fig. 2	M-126-490	B-490	Polyester	Black on White	1.800 (45.7)	0.600 (45.7)	-	180	R4300
B-492 FreezerBondz Polyester										
BMP51, 53	Fig. 24	M-118-492	B-492	Polyester	Black on White	1.000 (25.4)	0.375 (9.5)	0.375 (9.5) dia.	240	R6400
BMP51, 53	Fig. 24	M-120-492	B-492	Polyester	Black on White	1.000 (25.4)	0.500 (12.7)	0.375 (9.5) dia.	240	R6400
BMP51, 53	Fig. 24	M-117-492	B-492	Polyester	Black on White	1.000 (25.4)	0.500 (12.7)	0.440 (11.1) dia.	240	R6400
BMP51, 53	Fig. 26	M-82-492	B-492	Polyester	Black on White	0.375 (9.5) dia.	-	-	240	R6400
BMP51, 53	Fig. 26	M-83-492	B-492	Polyester	Black on White	0.500 (12.7) dia.	-	-	240	R6400
BMP51, 53	Fig. 33	MC-500-492	B-492	Polyester	Black on White	0.500 (12.7)	25 ft. (7.6 m)	-	1 roll (cont.)	R6400
BMP51, 53	Fig. 2	M-130-492	B-492	Polyester	Black on White	0.825 (20.9)	0.375 (9.5)	-	220	R6400
BMP51, 53	Fig. 2	M-130-492	B-492	Polyester	Black on White	0.825 (20.9)	0.375 (9.5)	-	220	R6400
BMP51, 53	Fig. 2	M-156-492	B-492	Polyester	Black on White	0.900 (22.8)	1.000 (25.4)	-	180	R6400
BMP51, 53	Fig. 2	M-156-492	B-492	Polyester	Black on White	0.900 (22.8)	1.000 (25.4)	-	180	R6400
BMP51, 53	Fig. 2	M-131-492	B-492	Polyester	Black on White	1.000 (25.4)	0.500 (12.7)	-	180	R6400
BMP51, 53	Fig. 2	M-131-492	B-492	Polyester	Black on White	1.000 (25.4)	0.500 (12.7)	-	180	R6400
BMP51, 53	Fig. 66	M-155-492	B-492	Polyester	Black on White	1.250 (31.7)	0.250 (6.3)	-	180	R6400
BMP51, 53	Fig. 2	M-78-492	B-492	Polyester	Black on White	1.900 (48.2)	1.000 (25.4)	-	100	R6400

Microscope Slide Labels (B-481 and B-488)

StainerBondz™ Labels are designed specifically to identify slides and to resist exposure to harsh chemicals during the slide staining process. They perform well in stains such as hematoxylin and eosin.

- **B-481 StainerBondz Polyester:** White polyester with extreme chemical resistance and withstands the rigors of typical deparaffinization, including ethanol, xylene and H and E staining process.
- **B-488 StainerBondz Polyester:** White polyester with moderate chemical resistance for short-term exposure to xylene, DMSO and ethanol.




Figure 2



Fits Printers	Figure	Catalog #	B#	Material	Color	Label Width A Inch (mm)	Label Height B Inch (mm)	Labels Per Roll	Ribbon in Cartridge
B-481 Polyester with extreme chemical-resistance									
BMP51, 53	Fig. 2	M-195-481	B-481	Polyester	Black on White	0.900 (22.8)	0.375 (9.5)	320	R6400
BMP51, 53	Fig. 2	M-194-481	B-481	Polyester	Black on White	0.900 (22.8)	0.750 (19.1)	320	R6400
BMP51, 53	Fig. 2	M-97-481	B-481	Polyester	Black on White	0.900 (22.8)	0.900 (22.9)	280	R6400
B-488 Polyester with moderate chemical-resistance									
BMP51, 53	Fig. 2	M-97-488	B-488	Polyester	Black on White	0.900 (22.8)	0.900 (22.9)	280	R4300
BMP51, 53	Fig. 2	M-81-488	B-488	Polyester	Black on White	1.900 (48.2)	0.250 (6.3)	160	R4300

Microcentrifuge and PCR Tube Labels (B-499 and B-7425)

Designed with ultra-thin material that prevents vials from jamming in centrifuges or racks. These labels withstand harsh temperatures and chemicals without falling off, fading or smearing.

- **B-499 Nylon Cloth:** Thick white nylon cloth for easy handling and conformability.
- **B-7425 Polypropylene:** Ideal for labeling dry, room temperature specimen containers. Temp. range: -196° C to 121° C (-320° F to 248° F). Chemical resistance to ethanol, DMSO, IPS, short term xylene, 10% formalin, 50% acetic acid and toluene.




Figure 2




Figure 24




Figure 26



Figure 33



Fits Printers	Figure	Catalog #	B#	Material	Color	Label Width A Inch (mm)	Label Height B Inch (mm)	Label Dia. C Inch (mm)	Labels Per Roll	Ribbon in Cartridge
B-499 Nylon Cloth										
BMP51, 53	Fig. 24	M-118-499	B-499	Nylon Cloth	Black on White	1.000 (25.4)	0.375 (9.5)	0.375 (9.5) dia.	240	R4300
BMP51, 53	Fig. 24	M-120-499	B-499	Nylon Cloth	Black on White	1.000 (25.4)	0.500 (12.7)	0.375 (9.5) dia.	240	R4300
BMP51, 53	Fig. 24	M-117-499	B-499	Nylon Cloth	Black on White	1.000 (25.4)	0.500 (12.7)	0.440 (11.1) dia.	240	R4300
BMP51, 53	Fig. 33	MC-1000-499	B-499	Nylon Cloth	Black on White	1.000 (25.4)	16 ft. (4.8 m)	-	1 roll (cont.)	R4300
BMP51, 53	Fig. 26	M-82-499	B-499	Nylon Cloth	Black on White	0.375 (9.5) dia.	-	-	240	R4300
BMP51, 53	Fig. 26	M-83-499	B-499	Nylon Cloth	Black on White	0.500 (12.7) dia.	-	-	240	R4300
BMP51, 53	Fig. 26	M-82-499-OR-BK	B-499	Nylon Cloth	Black on Orange	0.375 (9.5) dia.	-	-	240	R4300
BMP51, 53	Fig. 26	M-83-499-OR-BK	B-499	Nylon Cloth	Black on Orange	0.500 (12.7) dia.	-	-	240	R4300
BMP51, 53	Fig. 26	M-82-499-RD-BK	B-499	Nylon Cloth	Black on Red	0.375 (9.5) dia.	-	-	240	R4300
BMP51, 53	Fig. 26	M-83-499-RD-BK	B-499	Nylon Cloth	Black on Red	0.500 (12.7) dia.	-	-	240	R4300
BMP51, 53	Fig. 26	M-82-499-YL-BK	B-499	Nylon Cloth	Black on Yellow	0.375 (9.5) dia.	-	-	240	R4300
BMP51, 53	Fig. 26	M-83-499-YL-BK	B-499	Nylon Cloth	Black on Yellow	0.500 (12.7) dia.	-	-	240	R4300
B-7425 Polypropylene										
BMP51, 53	Fig. 24	M-118-7425	B-7425	Polypropylene	Black on White	1.000 (25.4)	0.375 (9.5)	0.375 (9.5) dia.	240	R4300
BMP51, 53	Fig. 2	M-31-7425	B-7425	Polypropylene	Black on White	1.500 (38.1)	1.000 (25.4)	-	250	R4300

Tissue Cassette Labels (B-482 and B-498)

- **B-482 Polyester Material:** White polyester label with superior resistance to tissue processing chemicals and embedding procedures. Use with the BSP™31 Label Attachment System for pre-process tissue cassette ID.
- **B-498 Repositionable Vinyl Cloth Material:** Removable white vinyl cloth for re-identification of post-process tissue cassettes or general lab applications. Can be applied directly onto the cassettes or on top of previous label.




Figure 2



Fits Printers	Figure	Catalog #	B#	Material	Color	Label Width A Inch (mm)	Label Height B Inch (mm)	Labels Per Roll	Ribbon in Cartridge
BMP51, 53	Fig. 2	M-127-482	B-482	Polyester	Black on White	1.05 (26.6)	0.250 (6.3)	360	R6400
BMP41, 51, 53	Fig. 2	M-11-498	B-498	Vinyl Cloth	Black on White	0.750 (12.7)	0.500 (19.1)	220	R6200

Color Polyester Labels (B-494)

Gloss white polyester with a color border printed on the label allows for differentiation of test specimens within user processes. Vial top labels are solid color. Resistant to common lab chemicals like ethanol and xylene.




Figure 2




Figure 24



Fits Printers	Figure	Catalog #	B#	Material	Color	Label Width A Inch (mm)	Label Height B Inch (mm)	Secondary Label C Inch (mm)	Labels Per Roll	Ribbon in Cartridge
BMP51	Fig. 24	M-118-494-BL	B-494	Polyester	Black on Blue	1.000 (25.4)	0.375 (9.5)	0.375 (9.5)	240	R6400
BMP51	Fig. 24	M-120-494-BL	B-494	Polyester	Black on Blue	1.000 (25.4)	0.500 (12.7)	0.375 (9.5)	240	R6400
BMP51	Fig. 2	M-131-494-BL	B-494	Polyester	Black on Blue	1.000 (25.4)	0.500 (12.7)	-	180	R6400
BMP51	Fig. 2	M-49-494-BL	B-494	Polyester	Black on Blue	1.000 (25.4)	1.000 (25.4)	-	260	R6400
BMP51	Fig. 24	M-118-494-GN	B-494	Polyester	Black on Green	1.000 (25.4)	0.375 (9.5)	0.375 (9.5)	240	R6400
BMP51	Fig. 24	M-120-494-GN	B-494	Polyester	Black on Green	1.000 (25.4)	0.500 (12.7)	0.375 (9.5)	240	R6400
BMP51	Fig. 2	M-131-494-GN	B-494	Polyester	Black on Green	1.000 (25.4)	0.500 (12.7)	-	180	R6400
BMP51	Fig. 2	M-49-494-GN	B-494	Polyester	Black on Green	1.000 (25.4)	1.000 (25.4)	-	260	R6400
BMP51	Fig. 24	M-118-494-OR	B-494	Polyester	Black on Orange	1.000 (25.4)	0.375 (9.5)	0.375 (9.5)	240	R6400
BMP51	Fig. 24	M-120-494-OR	B-494	Polyester	Black on Orange	1.000 (25.4)	0.500 (12.7)	0.375 (9.5)	240	R6400
BMP51	Fig. 2	M-131-494-OR	B-494	Polyester	Black on Orange	1.000 (25.4)	0.500 (12.7)	-	180	R6400
BMP51	Fig. 2	M-49-494-OR	B-494	Polyester	Black on Orange	1.000 (25.4)	1.000 (25.4)	-	260	R6400
BMP51	Fig. 24	M-118-494-PK	B-494	Polyester	Black on Pink	1.000 (25.4)	0.375 (9.5)	0.375 (9.5)	240	R6400
BMP51	Fig. 24	M-120-494-PK	B-494	Polyester	Black on Pink	1.000 (25.4)	0.500 (12.7)	0.375 (9.5)	240	R6400
BMP51	Fig. 2	M-131-494-PK	B-494	Polyester	Black on Pink	1.000 (25.4)	0.500 (12.7)	-	180	R6400
BMP51	Fig. 2	M-49-494-PK	B-494	Polyester	Black on Pink	1.000 (25.4)	1.000 (25.4)	-	260	R6400
BMP51	Fig. 24	M-118-494-RD	B-494	Polyester	Black on Red	1.000 (25.4)	0.375 (9.5)	0.375 (9.5)	250	R6400
BMP51	Fig. 24	M-120-494-RD	B-494	Polyester	Black on Red	1.000 (25.4)	0.500 (12.7)	0.375 (9.5)	240	R6400
BMP51	Fig. 2	M-131-494-RD	B-494	Polyester	Black on Red	1.000 (25.4)	0.500 (12.7)	-	180	R6400
BMP51	Fig. 2	M-49-494-RD	B-494	Polyester	Black on Red	1.000 (25.4)	1.000 (25.4)	-	260	R6400
BMP51	Fig. 24	M-118-494-YL	B-494	Polyester	Black on Yellow	1.000 (25.4)	0.375 (9.5)	0.375 (9.5)	240	R6400
BMP51	Fig. 24	M-120-494-YL	B-494	Polyester	Black on Yellow	1.000 (25.4)	0.500 (12.7)	0.375 (9.5)	240	R6400
BMP51	Fig. 2	M-131-494-YL	B-494	Polyester	Black on Yellow	1.000 (25.4)	0.500 (12.7)	-	180	R6400
BMP51	Fig. 2	M-49-494-YL	B-494	Polyester	Black on Yellow	1.000 (25.4)	1.000 (25.4)	-	260	R6400



Get the job done for less with a Printer Starter Kit

Voice and DataComm Starter Kit

Kit includes:

- Hard case, USB cable and AC power supply
- Self-laminating cable markers (M-21-427)
- Port, faceplate and general ID labels (M-30-422)
- Non-adhesive slide-in strips for punch blocks (MC-475-412)
- Rack and panel labels (MC-1000-595-YL-BK)
- 1.5 in. white label roll for general ID (MC-1500-595-WT-BK)

Catalog #	Description
BMP51-KIT-VD	Starter Kit with BMP51 Label Printer and Li-Ion Battery

Electrical ID Starter Kit

Kit includes:

- Hard case, USB cable and AC power supply
- Self-laminating wire markers (M-103-427)
- Wrap around wire markers (M-18-498)
- PermaSleeve® PS Heat-Shrink Wire Markers (M-187-1-342)
- Panel identification labels (MC-1500-595-OR-BK)
- 1.5 in. white label roll for general ID (MC-1500-595-WT-BK)

Catalog #	Description
BMP51-KIT-EL	Starter Kit with BMP51 Label Printer and Li-Ion Battery

Facility ID Starter Kit

Kit includes:

- Hard case, USB cable and AC power supply
- 1.5 in. yellow label roll with black ribbon (MC-1500-595-YL-BK)
- 1.5 in. white label roll with red ribbon (MC-1500-595-WT-RD)
- 1.5 in. green label roll with white ribbon (MC-1500-595-GN-WT)
- 1.5 in. white label roll with black ribbon (MC-1500-595-WT-BK)
- 2 in. x 1 in. labels for low surface energy labeling (M-20-483)

Catalog #	Description
BMP51-KIT-GI	Starter Kit with BMP51 Label Printer and Li-Ion Battery

Lab ID Starter Kit

Kit includes:

- Hard case, USB cable and AC power supply
- Vial and tube labels (M-156-492)
- Microplate labels (M-81-488)
- Top and side label set for vials and tubes (M-120-492)
- Removable die-cut labels for bottles, beakers, etc. (M-103-498)
- 1.5 in. white label roll for general ID (MC-1500-595-WT-BK)

Catalog #	Description
BMP51-KIT-LS	Starter Kit with BMP51 Label Printer and Li-Ion Battery

По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +(727)345-47-04

Беларусь +(375)257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: byb@nt-rt.ru || сайт: <https://brady.nt-rt.ru/>